

AN EYE TOWARDS THE FUTURE.

The world is developing quickly – and we have to keep up with it. That's why we've already adapted our most successful systems with an eye towards the future. Print speeds of 50 to 60 A4 pages per minute and top quality (1,200 x 1,200 dpi) meet the highest demands, increasing flexibility in paper handling and finishing. Security is assured with the Trusted Platform Module (TPM), a standard element, which encrypts confidential information on the device and is stored in a dedicated storage area. This storage area cannot be read from outside the TPM, meaning confidential information can be safely protected. Of course, we also take environmental concerns into account, and have increased energy efficiency and low noise emissions. Everything is possible.

HIGHLIGHTS:



Truly efficient: The systems feature output speeds of 50 and 60 pages per minute respectively. Original documents can be scanned and digitised at a rate of up to 220 images per minute, at 300 dpi in colour and b/w. The print quality is 1,200 x 1,200 dpi. The paper feeder holds up to 7,150 sheets in formats from A6R to SRA3 and paper weights from 52 to 300 g/m². Tailor your finishing according to the project: The finisher holds up to 4,000 sheet and can staple, hole-punch and even create brochures*.



Less is more: Using less paper is good, not only for your company budget, but also for the environment. Functions such as duplex printing and automatic skipping of blank pages underscore this line of thinking, saving resources such as paper, toner and time in your everyday workflows. Moreover, improved TEC values, low noise emissions and less waste thanks to durable components also make for a positive environmental balance. We're always thinking ahead.



The advantages of variety: If you want to keep up in the fast-paced working world, you need to be flexible. The 5057i and 6057i stand out in this regard. Starting with the new colour touch panel with its 10.1 inch screen and customisable function keys for better usability, the HyPAS is able to integrate external software solutions up to a professional finishing that leaves nothing to be desired.



Protection is a must: Security in office communication is a major challenge these days. That's why our systems already fulfill important safety standards in basic configuration. This security solution protects your confidential information: it overwrites and encrypts copy, scan and print data even before it's saved to disk. In addition, the memory area for output data is automatically wiped clean, preventing it from being restored.



DIGITAL MULTIFUNCTIONAL SYSTEM

5057i / 6057i

Copy / Print / Scan / Fax

A3

5057i / 6057i

TECHNICAL DATA



GENERAL

Type	Desktop
Function	Copy, print, scan, optional: fax
Print technology	Laser b/w
Original format	max A3 from platen glass
Copy/print speed	5057i: max 50 A4 pages/min and max 25 A3 pages/min 6057i: max 60 A4 pages/min and max 30 A3 pages/min
1st page (Copy/Print)	3.7/4.3 seconds* (5057i), 3.4/3.8 seconds* (6057i)
Warm-up time	17 seconds
Copy resolution	600 x 600 dpi
Greyscales	256
Paper feed	2 x 500 sheet universal cassettes (cassette 1: A6R-A4, cassette 2: A6R-SRA3 [320 x 450 mm]), 150 sheet multi-bypass (A6R-SRA3, Banner [305 x 1,219 mm]), SRA3 and banner only for printing
Paper weights	Universal cassette 52-300 g/m ² , multi-bypass 52-300 g/m ² , duplex 64-256 g/m ²
Paper output	500 sheet A4
System memory	4 GB RAM, 8 GB SSD/320 GB HDD**
Continuous copying	1-9,999 copies
Zoom	25 %-400 % in steps of 1 %
Functions	Adjustable capacitive colour touch screen (10.1 inch), duplex, 1,000 management codes, skip blank pages, motion sensor etc.

DIMENSIONS/WEIGHT

Dimensions	790 x 602 x 665 mm (H x W x D)
Weight	approx. 83 kg

ENVIRONMENT

Mains voltage	220/240 V, 50/60 Hz
Power consumption	approx. 1,750 W max, approx. 758/878 W in operation (5057i/6057i), approx. 50 W in stand-by mode, approx. 0.7 W in sleep mode, TEC value: 2.365/3.016 kWh/week (5057i/6057i)
Safety	GS/TÜV, CE, Trusted Platform Module (TPM)

PRINT SYSTEM

Type	Integrated within the system
Print format	A6R-SRA3
Print resolution	600 x 600 dpi, max 1,200 x 1,200 dpi
Processor	Freescale QorIQ T1024 (Dual Core) 1.2 GHz
Interfaces	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC

PRINT SYSTEM

Network protocols	TCP/IP, Net BEUI
Operating systems	Windows 7/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare***, Linux, Mac ex OS 10.9
Emulations	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, PDF 1.7, PRESCRIBE IIe
Functions	USB direct printing, PDF/XPS direct printing, printing of e-mails, private printing, barcode printing, Mobile Print (Android/iOS)/Apple AirPrint, Google Cloud Print

SCAN SYSTEM

Scan type	CCD colour and b/w
Scan format	max A3
Scan speed	max 120 (simplex) or 220 (duplex) A4 originals/min in colour and b/w with DP-7130 (300 dpi)
Scan resolution	200 dpi, 300 dpi, 400 dpi, 600 dpi
Scan mode	Photo, text, photo/text, optimised for OCR
File types	TIFF, PDF, PDF/A, high compression PDF, encrypted PDF, JPEG, XPS, Open XPS
Interface	10/100/1000BaseTX
Network protocol	TCP/IP
Operating systems	Windows 7/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016
Functions	Scan to SMB, scan to e-mail, scan to FTP, scan to USB, TWAIN scan, WIA scan, SMTP authentication, LDAP

OPTION FAX SYSTEM 12

Compatibility	Super G3
Original format	max A3
Modem speed	33.6 kbps
Transmission speed	3 seconds or less using JBIG
Compression method	JBIG, MMR, MR, MH
Fax resolution	Standard (200 x 100 dpi), fine (200 x 200 dpi), super fine (200 x 400 dpi), ultra fine (400 x 400 dpi), 600 x 600 dpi
Fax memory	170 MB
Abbreviated dial	2,000 numbers
One touch dial	1,000 numbers
Group dial	500 numbers
Operating systems	Windows 7/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016
Functions	Network fax driver, automatic redialling, delayed transmission, max 2 fax kits for parallel transmission and reception

OPTIONS

Original feeder	DP-7100 document processor with automatic reverse function (A6R-A3, capacity: 140 sheet A4, paper weight 35-160 g/m ²), DP-7110 document processor with simultaneous duplex scanning (A6R-A3, capacity: 270 sheet A4, paper weight 35-220 g/m ²), DP-7130 document processor with simultaneous duplex scanning and ultrasonic sensor for multi-feed detection (A6R-A3, capacity: 270 sheet A4, paper weight 35-220 g/m ²)
Platen cover	Platen cover type E (if document processor is not installed)
Finisher	DF-7100 internal finisher (capacity: 500 sheet A4, stapling max 50 sheet A4), DF-7120 (capacity: 1,000 sheet A4, stapling max 50 sheet A4), DF-7110 (capacity: 4,000 sheet A4, stapling max 65 sheet A4), DF-7130 (capacity: 4,000 sheet A4, stapling max 100 sheet A4), PH-7120 hole punch unit for DF-7100, PH-7C hole punch unit for DF-7120/7110/7130, BF-730 brochure module for DF-7110 (max 20 sheet saddle stitching and folding A4/A3, tri-folding max 5 sheet A4), BF-9100 brochure module for DF-7130 (max 20 sheet saddle stitching and folding A4/SRA3, tri-folding max 5 sheet A4), MT-730 (B) multi tray for DF-7110
Job Separator	JS-7100: 100 sheet
Paper feed	PF-7100 (2 x 500 sheet universal cassettes [A5R-SRA3]), PF-7110 (2 x 1,500 sheet large capacity cassette [A4]), PF-7120 (3,000 sheet large capacity tray [A4], side deck)
Other options	Scan extension kit (A), Internet fax kit (A), Card authentication kit (B), Keyboard holder 10, Banner guide 10, UG-33 ThinPrint® kit, UG-34 Emulation option kit, IB-50 Gigabit Ethernet card, IB-51 WLAN card, IB-35 WLAN card, DT-730 (B) Document tray, NK-7120 Numeric Keyboard (10 keys), cabinet no. 76

*Depending on operating status.

**For copy, print, scan, fax.

***optional

Specifications subject to change without notice.

Image shows machine with optional accessories.

The 5057i and the 6057i are manufactured in accordance with the requirements of the Energy Star Program.

UTAX has been a trade mark for professional office technology since 1961. As the partner of a German wide dealer network and international distribution, we are specialised in the distribution and integration of printing, copying and multifunctional systems in corporate IT and public sector, amongst others. With the MDS solution UTAX smart for example, output systems can be controlled regardless of the manufacturer and the infrastructure can be optimised in line with demands. UTAX recommends the use of original UTAX accessories for trouble-free operation of your system. For recommended print media refer to the user manual. UTAX and the UTAX logo are registered trade marks of TA Triumph-Adler GmbH. All other brand names referred to are registered trade marks of the respective manufacturers.

